

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
23 December 2004 (23.12.2004)

PCT

(10) International Publication Number
WO 2004/112432 A1

(51) International Patent Classification⁷: **H04S 3/00**

(21) International Application Number:

PCT/IB2004/050878

(22) International Filing Date: 9 June 2004 (09.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03101758.5 16 June 2003 (16.06.2003) EP

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]**;
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **WEISER, Thomas**
[AT/AT]; Triester Strasse 64, A-1101 Vienna (AT).


(74) Agent: **RÖGGLA, Harald**; Philips Intellectual Property
& Standards, Triester Strasse 64, A-1101 Vienna (AT).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: **DEVICE AND METHOD FOR LOCATING A ROOM AREA**



(57) Abstract: In a circuit (15) for a locating device (14) for locating a room area (12) from which an optical locating signal (LS) generated and emitted by means of a locating-signal generating stage (13) originates, there is provided firstly a reception stage (17) that is arranged at a distance (R) from the room area (12) to be located and that is designed to receive, optically, the optical locating signal (LS) that can be fed to it from the room area (12), and there is provided secondly a determining stage (26) that, by using the optical locating signal (LS) that is received, is designed to determine and emit an item of room-area locating information (S1) that represents the distance between the receiving stage (17) and the room area (12).



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.